



A NEW STANDARD OF POWER

# Half Rack UPS™

Half Width Footprint. Lightweight. High Power Density.

## Power Has Never Been More Portable

Acumentrics uses advanced technologies in power conversion and high-performance digital control to optimize the SWaP of the COTS 1000W Rugged Half Rack UPS™ family.

- ▶ Designed to support “At the Quick Halt” and “On the Move” mounted and dismounted tactical missions
- ▶ Designed to work with small form factor modules, racks and cases



1U AHB1001



2U AHB1002



3U AHB1003

COMING  
SOON

## Half Rack UPS Specifications

P/N	INPUTS	OUTPUTS	SIZE	ISOLATED	N+1	VAC IN	Freq IN (hz)	VAC OUT	Freq OUT (hz)	VDC IN	VDC OUT	POWER OUT	COMMS
AHB1001	AC	DC	1U	No	No	100-265	47-63	N/A	N/A	N/A	20-29	1kW	SNMP and RS232
AHB1002	AC/DC	DC	2U	No	No	100-265	47-63	N/A	N/A	22-32	20-48	1kW	SNMP and RS232
AHB1003*	AC/DC	AC/DC	3U	No	No	100-265	47-63	115	60	22-32	20/29	1kW (750W AC)	SNMP and RS232
AWB1002-AC*	AC/DC	AC	2U	Yes	Yes	80-264	47-440	115/230	50/60	22-32	N/A	1kW	SNMP and RS232
AWB1002-DC*	AC/DC	DC	2U	Yes	Yes	80-264	47-440	N/A	N/A	20-32	24/28/48	500W	SNMP and RS232

\* COMING SOON

### MIL-STDs and Certifications

- ▶ EMI/EMC: MIL-STD-461G: CE102, CS101, CS114, CS115, CS116, CS118, RE102, RS103
- ▶ Environmental: MIL-STD-810H - Shock: 20G, 11 ms, Sawtooth; Vibration: 5-500Hz, 2Grms, Random
- ▶ Transport: UN-DOT 38.3
- ▶ CE (coming soon)

### Environmental

- ▶ Operating: -20 °C to 55 °C
- ▶ Storage: -40 °C to 60 °C
- ▶ Humidity: up to 95% (non-condensing)

### Mechanical Specs

- ▶ Chassis Length/Width: 15" L / 9.4" W

### Battery Runtime

- ▶ Typical Run Times:
  - 20 minutes @ 400W load
  - 6 minutes @ 1000W load
- ▶ Recharge Time: 3 hours to 90% of present capacity

### 1U AHB1001



Front View



Rear View

### 2U AHB1002



Front View



Rear View

### 3U AHB1003



Front View



Rear View

### Contact a Representative

**East USA:** Wade Ichinose | [wichinose@acumentrics.com](mailto:wichinose@acumentrics.com) | +1 (781) 815-6048

**West USA:** Jason Quinten | [jquinten@acumentrics.com](mailto:jquinten@acumentrics.com) | +1 (781) 824-3973

**International:** Nick Ouellette | [nouvellette@acumentrics.com](mailto:nouvellette@acumentrics.com) | +1 (781) 885-4429

