

A NEW STANDARD OF POWER Half Rack UPS™

Half Width Footprint. Lightweight. High Power Density.

Power Has Never Been More Portable

Acumentrics uses advanced technologies in power conversion and high-performance digital control to optimize the SWaP of the COTS **1000W** Rugged Half Rack UPS[™] family.

- Designed to support "At the Quick Halt" and "On the Move" mounted and dismounted tactical missions
- Designed to work with small form factor modules, racks and cases

1U AHB1001



PROTOTYPES AVAILABLE





3U AHB1003

Half Rack UPS Specifications

TRUSTED POWER INNOVATIONS®

2:

GENERAL SPECIFICATIONS						INPUTS			OUTPUTS				
P/N	INPUTS	OUTPUTS	SIZE	ISOLATION	N+1	VAC IN	Freq IN (hz)	VDC IN	VAC OUT	Freq OUT (hz)	VDC OUT	POWER	COMMS
AHB1001	AC	DC	1U	AC to DC	No	100-265	47-63	N/A	N/A	N/A	28/48	1kW	SNMP and RS232
AHB1002	AC/DC	DC	2U	AC to DC	No	100-265	47-63	22-32	N/A	N/A	28	1kW	SNMP and RS232
AHB1003*	AC/DC	AC/DC	3U	AC to DC	No	100-265	47-63	22-32	115	60	28	1kW (750W AC)	SNMP and RS232
AWB1002-AC*	AC/DC	AC	2U	Full	Yes	80-265	47-440	22-32	115/230	50/60	N/A	1kW	SNMP and RS232
AWB1002-DC*	AC/DC	DC	2U	Full	Yes	80-265	47-440	22-32	N/A	N/A	24/28/48	500W	SNMP and RS232
AWB1002- AC/DC**	AC/DC	AC/DC	2U	Full	Yes	80-265	47-440	22-32	115/230	50/60	24/28/48	TBD	SNMP and RS232

** COMING SOON

*Prototypes Available

MIL-STDs and Certifications

- EMI/EMC: MIL-STD-461G: CE102, CS101, CS114, CS115, CS116, CS118, RE102, RS103
- Environmental: MIL-STD-810H Shock: 20G, 11 ms, Sawtooth; Vibration: 5-500Hz, 2Grms, Random
- Transport: UN-DOT 38.3
- CE (coming soon)

Environmental

- Operating: -20 °C to 55 °C
- Storage: -40 °C to 60 °C
- Humidity: up to 95% (non-condensing)

Mechanical Specs

Chassis Length/Width: 15" L / 9.4" W

Battery Runtime

- Typical Run Times:
 - 20 minutes @ 400W load
 - 6 minutes @ 1000W load
- Recharge Time: 3 hours to 90% of present capacity



2U AHB1002



Contact a Representative

East USA: Wade Ichinose | wichinose@acumentrics.com | +1 (781) 815-6048 West USA: Jason Quinten | jquinten@acumentrics.com | +1 (781) 824-3973 International: Nick Ouellette | nouellette@acumentrics.com | +1 (781) 885-4429

